

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem 2K FILLER VARIO PLUS light grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1AUS DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Carsystem 2K FILLER VARIO PLUS light grey  
Product code : CS152057

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Body filler/stopper, Paints  
Recommended restrictions  
on use : Reserved for industrial and professional use.  
Industrial use, professional use

#### 1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH  
Esinger Steinweg 50  
25436 Uetersen  
Germany  
info@vosschemie.de

Telephone : 04122 717 0  
Telefax : 04122 717158

**Responsible Department** : Laboratory  
  
04122 717 0  
sds@vosschemie.de

#### 1.4 Emergency telephone

Telephone : Giftinformationszentrum (GIZ)-Nord, Göttingen, Deutschland  
0551 19240

#### **IMPORTED BY:**

**Sydney Automotive Paints & Equipment PTY LTD Unit A3, 366 Edgar St. Condell  
Park NSW 2200 AUSTRALIA, Tel. +02 9772 9000 , +02 9772 9001 .**

**Emergency telephone number: If poisoning occurs contact a doctor or Poisons  
Information Centre. Phone Australia 131 126, New Zealand 0800 764 766**

## Carsystem 2K FILLER VARIO PLUS light grey

Version 1.1AUS DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe mist or vapors.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

##### **Response:**

P314 Get medical advice/ attention if you feel unwell.

##### **Disposal:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version 1.1AUS DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022 Date of first issue: 20.07.2022

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

### Hazardous ingredients which must be listed on the label:

reaction mass of ethylbenzene and m-xylene and p-xylene  
xylene

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Mixture

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
reaction mass of ethylbenzene and m-xylene and p-xylene	Not Assigned 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304  specific concentration limit STOT RE 2 >= 10 %	>= 10 - <= 15
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 2,5 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version  
1.1AUS

DE / EN

Revision Date:  
12.10.2023

Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

		<p>STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Central nervous system, Liver, Kidney) Asp. Tox. 1; H304 Aquatic Chronic 3; H412</p> <hr/> <p>Acute toxicity estimate</p> <p>Acute inhalation toxicity (vapor): 11 mg/l</p>	
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - <= 5
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - <= 5
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 1 - <= 5
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	<p>Aquatic Acute 1; H400 Aquatic Chronic 1; H410</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1</p>	>= 1 - < 2,5
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	<p>Aquatic Acute 1; H400 Aquatic Chronic 1; H410</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1</p>	>= 0,25 - < 1

For explanation of abbreviations see section 16.

**Carsystem 2K FILLER VARIO PLUS light grey**

Version	Revision Date:	Date of last issue: 20.07.2022
1.1AUS DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

**SECTION 4: First aid measures****4.1 Description of first-aid measures**

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
Move out of dangerous area.  
Take off contaminated clothing and shoes immediately.  
Do not leave the victim unattended.  
Symptoms of poisoning may appear several hours later.  
Show this material safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing  
  
First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Keep eye wide open while rinsing.  
If easy to do, remove contact lens, if worn.  
Consult a physician.
- If swallowed : Do NOT induce vomiting.  
Call a physician immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

- Risks : Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure.  
  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1AUS DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry powder  
Water spray jet  
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes. In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation, especially in confined areas.  
Remove all sources of ignition.  
Do not smoke.  
Avoid contact with skin, eyes and clothing.  
In the case of vapor formation use a respirator with an approved filter.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1AUS DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

### 6.2 Environmental precautions

Environmental precautions : Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Do not flush into surface water or sanitary sewer system.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.  
Do not flush with water.

### 6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Wear personal protective equipment.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Keep away from heat and sources of ignition. Protect from moisture. Keep away from direct sunlight.

Advice on common storage : Keep away from food and drink.  
Incompatible with oxidizing agents.  
Incompatible with strong acids and bases.

Storage class (TRGS 510) : 3

### 7.3 Specific end use(s)

Specific use(s) : No data available

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**Carsystem 2K FILLER VARIO PLUS light grey**Version  
1.1AUS DE / ENRevision Date:  
12.10.2023Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
xylylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption			
n-butyl acetate	123-86-4	AGW	62 ppm 300 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 270 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m <sup>3</sup>	2000/39/EC



**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE****Carsystem 2K FILLER VARIO PLUS light grey**Version  
1.1AUS DE / ENRevision Date:  
12.10.2023Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

	Further information: Identifies the possibility of significant uptake through the skin, Indicative		
	AGW	20 ppm 88 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)		
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		

**Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
ethylbenzene	100-41-4	mandelic acid + phenylglyoxylic acid: 250 mg/g Creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

Substance name	End Use	Routes of exposure	Potential health effects	Value
xylene	Workers	Inhalation	Long-term systemic effects, Long-term local effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects, Acute local effects	442 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	65,3 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects, Acute local effects	260 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	12,5 mg/kg bw/day
	n-butyl acetate	Workers	Inhalation	Long-term systemic effects, Long-term local effects
	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects, Acute systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	35,7 mg/m <sup>3</sup>

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE****Carsystem 2K FILLER VARIO PLUS light grey**Version  
1.1AUS DE / ENRevision Date:  
12.10.2023Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects, Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects, Acute systemic effects	2 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	83 mg/kg
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	83 mg/kg
	Consumers	Oral	Long-term systemic effects	0,83 mg/kg

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

Substance name	Environmental Compartment	Value	
xylene	Fresh water	0,327 mg/l	
	Sea water	0,327 mg/l	
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)	
	Sea sediment	12,46 mg/kg dry weight (d.w.)	
	Soil	2,31 mg/kg dry weight (d.w.)	
	Sewage treatment plant (STP)	6,58 mg/l	
	n-butyl acetate	Fresh water	0,18 mg/l
		Sea water	0,018 mg/l
		Fresh water sediment	0,981 mg/kg dry weight (d.w.)
Sea sediment		0,098 mg/kg dry weight (d.w.)	
Sewage treatment plant (STP)		35,6 mg/l	
2-methoxy-1-methylethyl acetate	Soil	0,09 mg/kg dry weight (d.w.)	
	Fresh water	0,635 mg/l	
	Sea water	0,064 mg/l	
	Sewage treatment plant (STP)	100 mg/l	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version 1.1AUS DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022 Date of first issue: 20.07.2022

	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sea sediment	0,329 mg/kg dry weight (d.w.)
	Soil	0,29 mg/kg dry weight (d.w.)
trizinc bis(orthophosphate)	Fresh water	0,014 mg/l
	Sea water	0,0072 mg/l
	Fresh water sediment	0,1469 mg/kg dry weight (d.w.)
	Sea sediment	0,162 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	0,1 mg/l
	Soil	83,1 mg/kg dry weight (d.w.)
zinc oxide	Fresh water	0,0206 mg/l
	Sea water	0,0061 mg/l
	Sewage treatment plant (STP)	0,1 mg/l
	Fresh water sediment	117,8 mg/kg
	Sea sediment	56,5 mg/kg
	Soil	35,6 mg/kg

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

#### Hand protection

Material : Fluorinated rubber  
Break through time : > 480 min  
Glove thickness : >= 0,4 mm  
Directive : DIN EN 374  
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.  
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version 1.1AUS DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

Filter type : Combined particulates and organic vapor type (A-P)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
Avoid contact with the skin and the eyes.  
Use only with adequate ventilation.

### Environmental exposure controls

Soil : Avoid subsoil penetration.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : paste

Color : gray

Odor : characteristic

Odor Threshold : not determined  
not determined

Melting point/range : not determined

Boiling point/boiling range : 137 °C

Upper explosion limit / Upper flammability limit : Upper explosion limit  
15 %(V)

Lower explosion limit / Lower flammability limit : Lower explosion limit  
1 %(V)

Flash point : 24 °C

Autoignition temperature : not determined

pH : Not applicable substance/mixture is non-soluble (in water)

Viscosity  
Viscosity, dynamic : not determined  
Viscosity, kinematic : not determined

Solubility(ies)  
Water solubility : immiscible

Partition coefficient: n-octanol/water : not determined

Vapor pressure : 10,7 hPa (20 °C)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version 1.1AUS DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

---

Density : 1,44 - 1,56 g/cm<sup>3</sup> (20 °C)

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if used as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Incompatible with strong acids and bases.  
Reaction with strong oxidizing agents.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases  
Strong oxidizing agents

### 10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

#### reaction mass of ethylbenzene and m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 - 4.000 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1AUS DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

Acute inhalation toxicity : LC50 (Rat, male): 6350 - 6700 ppm  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Regulation (EC) No. 440/2008, Annex, B.2

Acute dermal toxicity : LD50 Dermal (Rabbit): 12.126 mg/kg

### **xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment

Acute dermal toxicity : LD50 (Rabbit): > 1.700 mg/kg

### **n-butyl acetate:**

Acute oral toxicity : LD50 (Rat): 10.760 mg/kg  
Method: OECD Test Guideline 423

Acute inhalation toxicity : LD50 (Rat): > 21 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): 14.112 mg/kg  
Method: OECD Test Guideline 402

### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): 6.190 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg  
Method: OECD Test Guideline 402

### **ethylbenzene:**

Acute oral toxicity : LD50 (Rat): 3.500 mg/kg

### **trizinc bis(orthophosphate):**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

### **zinc oxide:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version		Revision Date:	Date of last issue: 20.07.2022
1.1AUS	DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

### **Skin corrosion/irritation**

Causes skin irritation.

#### **Components:**

#### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

Result : Skin irritation

#### **xylene:**

Result : Skin irritation

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Components:**

#### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

Result : Moderate eye irritation

#### **xylene:**

Result : Moderate eye irritation

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT-single exposure**

May cause respiratory irritation.

#### **Components:**

#### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version 1.1AUS DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

---

### **xylene:**

Assessment : May cause respiratory irritation.

### **2-methoxy-1-methylethyl acetate:**

Routes of exposure : Oral  
Target Organs : Central nervous system  
Assessment : May cause drowsiness or dizziness.

### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

### **Components:**

#### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

### **xylene:**

Target Organs : Central nervous system, Liver, Kidney  
Assessment : May cause damage to organs through prolonged or repeated exposure.

### **ethylbenzene:**

Target Organs : hearing organs  
Assessment : May cause damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

### **xylene:**

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1AUS DE / EN	12.10.2023	Date of first issue: 20.07.2022

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

Toxicity to fish	: LC50 (Fish): 2,6 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: LC50 (Daphnia dubia (Water flea)): 1 mg/l Exposure time: 24 h Method: OECD Test Guideline 202  EC50 (Daphnia dubia (Water flea)): 165 mg/l Exposure time: 24 h
Toxicity to algae/aquatic plants	: EC50 (algae): 2,2 mg/l Exposure time: 72 h Method: OECD Test Guideline 201  IC50 (algae): 1 - 10 mg/l Exposure time: 72 h
Toxicity to microorganisms	: EC50 (Bacteria): 1 - 10 mg/l

##### **Ecotoxicology Assessment**

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

##### **xylene:**

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (green algae)): 4,6 mg/l Exposure time: 72 h Test Type: Growth inhibition Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC: > 1,3 mg/l Exposure time: 56 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 0,96 mg/l Exposure time: 7 d Species: Ceriodaphnia dubia (water flea) Method: Regulation (EC) No. 440/2008, Annex, C.20

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version 1.1AUS DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

---

### **n-butyl acetate:**

- Toxicity to fish : (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647,7 mg/l  
Exposure time: 72 h
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### **2-methoxy-1-methylethyl acetate:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: Regulation (EC) No. 440/2008, Annex, C.2
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC: 47,5 mg/l  
Exposure time: 14 d  
Species: Oryzias latipes (Orange-red killifish)  
Method: OECD Test Guideline 204
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: >= 100 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### **ethylbenzene:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,2 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,8 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic : EC50 (Scenedesmus capricornutum (fresh water algae)): 4,6

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1AUS DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

plants : mg/l  
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1 mg/l  
Species: Ceriodaphnia dubia (water flea)

### **trizinc bis(orthophosphate):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,169 mg/l  
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC: 0,044 mg/l  
Exposure time: 72 d  
Species: Oncorhynchus mykiss (rainbow trout)

M-Factor (Chronic aquatic toxicity) : 1

### **zinc oxide:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 3,31 mg/l  
End point: mortality  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 0,76 mg/l  
End point: mortality  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : IC50 (Pseudokirchneriella subcapitata (green algae)): 0,136 mg/l  
End point: Growth rate  
Exposure time: 72 h  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

Toxicity to fish (Chronic toxicity) : NOEC: 0,44 mg/l  
End point: mortality  
Exposure time: 72 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,058 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version 1.1AUS DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

---

Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

### 12.2 Persistence and degradability

#### Components:

##### **xylene:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301

##### **n-butyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d

##### **2-methoxy-1-methylethyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 90 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **ethylbenzene:**

Biodegradability : Result: rapidly degradable  
Biodegradation: 79 %  
Exposure time: 10 d

### 12.3 Bioaccumulative potential

#### Components:

##### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

Partition coefficient: n-octanol/water : log Pow: 3,2 (20 °C)

##### **xylene:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Bioconcentration factor (BCF): 25,9

Partition coefficient: n-octanol/water : log Pow: 3,155 (20 °C)

##### **n-butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)  
Method: OECD Test Guideline 117

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version 1.1AUS DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

---

### **2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)  
pH: 6,8  
Method: OECD Test Guideline 117

### **ethylbenzene:**

Partition coefficient: n-octanol/water : log Pow: 3,6 (20 °C)

### **trizinc bis(orthophosphate):**

Partition coefficient: n-octanol/water : Remarks: Not applicable

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **12.6 Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **12.7 Other adverse effects**

#### **Product:**

Additional ecological information : No data available

---

## **SECTION 13: Disposal considerations**

### **13.1 Waste treatment methods**

Product : Do not dispose of with domestic refuse.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
Dispose of in accordance with local regulations.  
Send to a licensed waste management company.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1AUS DE / EN	12.10.2023	Date of first issue: 20.07.2022

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Store containers and offer for recycling of material when in accordance with the local regulations.  
Packaging that is not properly emptied must be disposed of as the unused product.  
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:  
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADG	: UN 1263
ADN	: UN 1263
ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263
IATA	: UN 1263

#### 14.2 UN proper shipping name

ADG	: PAINT
ADN	: PAINT
ADR	: PAINT
RID	: PAINT
IMDG	: PAINT (trizinc bis(orthophosphate), zinc oxide)
IATA	: PAINT

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADG	: 3	
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version 1.1AUS DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

### 14.4 Packing group

#### ADG

Packing group : III

#### ADN

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

#### ADR

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

#### RID

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

#### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

#### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

#### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADG

Environmentally hazardous : yes

#### ADN

Environmentally hazardous : yes

#### ADR

Environmentally hazardous : yes

#### RID

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version 1.1AUS DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022 Date of first issue: 20.07.2022

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: < 540 g/l  
VOC content for the product in a ready to use condition.

### Other regulations:



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem 2K FILLER VARIO PLUS light grey

Version 1.1AUS DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022 Date of first issue: 20.07.2022

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

This Product is considered compliant to AIIIC (Australian Inventory of Industrial Chemicals).

## SECTION 16: Other information

### Full text of H-Statements

H225 : Highly flammable liquid and vapor.  
H226 : Flammable liquid and vapor.  
H304 : May be fatal if swallowed and enters airways.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Skin Irrit. : Skin irritation  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
TRGS 903 : c - Biological limit values  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
2019/1831/EU / TWA : Limit Value - eight hours  
2019/1831/EU / STEL : Short term exposure limit  
DE TRGS 900 / AGW : Time Weighted Average

## Carsystem 2K FILLER VARIO PLUS light grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1AUS DE / EN	12.10.2023	Date of first issue: 20.07.2022

ADG – Australian Dangerous Goods; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx – Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration as- sociated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Ef- fect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic sub- stance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Re- striction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Further information****Classification of the mixture:**

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 2	H411

**Classification procedure:**

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.