

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version 1.1AU DE / EN Revision Date: 04.09.2024 Date of last issue: 21.09.2023
Date of first issue: 29.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CAM Anti Chip Coat grey
Product code : 126.083

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Solvent-borne coatings, Corrosion inhibitor
Recommended restrictions on use : Reserved for industrial and professional use.
Industrial use, professional use

1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH
Esinger Steinweg 50
25436 Uetersen
Germany
info@vosschemie.de
Telephone : 04122 717 0
Telefax : 04122 717158
Responsible Department : Laboratory
04122 717 0
sds@vosschemie.de

1.4 Emergency telephone:

Giftinformationszentrum (GIZ)-Nord, Göttingen, Deutschland 0551 19240

1.5 Details of the supplier / Importer of the safety data sheet

Importer : SYDNEY AUTOMOTIVE PAINTS & EQUIPMENT
UN IT 3A, 366 EDGAR ST Condell Park, NSW 2200
Company PH: 02 9772 9000 FAX: 02 9772 9001
EMAIL: reception@sape.com.au

Emergency telephone number: Poison Information Centre Call 13 11 26
(Australia)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version
1.1AU

DE / EN

Revision Date:
04.09.2024

Date of last issue: 21.09.2023
Date of first issue: 29.07.2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--|--|
| Flammable liquids, Category 2 | H225: Highly flammable liquid and vapor. |
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Eye irritation, Category 2 | H319: Causes serious eye irritation. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |
| Long-term (chronic) aquatic hazard, Category 2 | H411: Toxic to aquatic life with long lasting effects. |

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapors.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version

1.1AU

DE / EN

Revision Date:

04.09.2024

Date of last issue: 21.09.2023

Date of first issue: 29.07.2022

easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous ingredients which must be listed on the label:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes
ethyl acetate

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|--|---|--|--------------------------|
| Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes | 64742-49-0 927-510-4 01-2119475515-33 | Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 | >= 10 - < 25 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version
1.1AU

DE / EN

Revision Date:
04.09.2024

Date of last issue: 21.09.2023
Date of first issue: 29.07.2022

| | | | |
|---|---|---|--------------|
| ethyl acetate | 141-78-6 205-500-4 607-022-00-5 01-2119475103-46 | Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066 | >= 10 - < 25 |
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | Not Assigned 921-024-6 01-2119475514-35 | Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 | >= 5 - < 10 |
| Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics | Not Assigned 920-750-0 01-2119473851-33 | Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066 | >= 5 - < 10 |
| Hydrocarbons, C9, Aromatics | Not Assigned 918-668-5 01-2119455851-35 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066 | >= 3 - < 5 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
Show this material safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

| | | |
|---------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 21.09.2023 |
| 1.1AU DE / EN | 04.09.2024 | Date of first issue: 29.07.2022 |

- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Keep eye wide open while rinsing.
If easy to do, remove contact lens, if worn.
Consult a physician.
- If swallowed : Do NOT induce vomiting.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder
Water spray jet
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
- Hazardous combustion products : Hazardous decomposition products due to incomplete combustion
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

CAM Anti Chip Coat grey

Version 1.1AU DE / EN Revision Date: 04.09.2024 Date of last issue: 21.09.2023
Date of first issue: 29.07.2022

5.3 Advice for firefighters

- Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes. In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
-

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Wear personal protective equipment.
Evacuate personnel to safe areas.
Ensure adequate ventilation, especially in confined areas.
Remove all sources of ignition.
Do not smoke.
Avoid contact with skin, eyes and clothing.
In the case of vapor formation use a respirator with an approved filter.

6.2 Environmental precautions

- Environmental precautions : Prevent spreading over a wide area (e.g., by containment or oil barriers).
Do not flush into surface water or sanitary sewer system.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Keep container closed when not in use.
Provide sufficient air exchange and/or exhaust in work rooms.
Wear personal protective equipment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version 1.1AU DE / EN Revision Date: 04.09.2024 Date of last issue: 21.09.2023
Date of first issue: 29.07.2022

Use only in well-ventilated areas.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Keep away from heat and sources of ignition. Protect from moisture. Keep away from direct sunlight.

Advice on common storage : Keep away from food and drink.

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---------------|----------|--|------------------------------------|-------------|
| ethyl acetate | 141-78-6 | STEL | 400 ppm 1.468 mg/m ³ | 2017/164/EU |
| | | Further information: Indicative | | |
| | | TWA | 200 ppm 734 mg/m ³ | 2017/164/EU |
| | | Further information: Indicative | | |
| | | AGW | 200 ppm 730 mg/m ³ | DE TRGS 900 |
| | | Peak-limit category: 2;(I) | | |
| | | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Routes of exposure | Potential health effects | Value |
|---|---------|--------------------|----------------------------|------------------------|
| Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes | Workers | Inhalation | Long-term systemic effects | 2085 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 300 mg/kg bw/day |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version
1.1AU

DE / EN

Revision Date:
04.09.2024

Date of last issue: 21.09.2023
Date of first issue: 29.07.2022

| | | | | |
|---|-----------|--------------------|---|------------------------|
| | Consumers | Inhalation | Long-term systemic effects | 447 mg/m ³ |
| | Consumers | Skin contact | Long-term systemic effects | 149 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 149 mg/kg bw/day |
| ethyl acetate | Workers | Inhalation | Long-term systemic effects, Long-term local effects | 734 mg/m ³ |
| | Workers | Inhalation | Acute systemic effects, Acute local effects | 1468 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 63 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects, Long-term local effects | 367 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects, Acute local effects | 734 mg/m ³ |
| | Consumers | Skin contact | Long-term systemic effects | 37 mg/kg bw/day |
| | Consumers | Ingestion | Long-term systemic effects | 4,5 mg/kg bw/day |
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | Workers | Inhalation | Long-term systemic effects | 2035 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 773 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 608 mg/m ³ |
| | Consumers | Skin contact, Oral | Long-term systemic effects | 699 mg/kg |
| Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics | Workers | Inhalation | Long-term systemic effects | 2035 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 773 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 608 mg/m ³ |
| | Consumers | Skin contact, Oral | Long-term systemic effects | 699 mg/kg |
| Hydrocarbons, C9, Aromatics | Workers | Inhalation | Long-term systemic effects | 150 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 25 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 11 mg/kg bw/day |
| | Consumers | Skin contact | Long-term systemic effects | 11 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 32 mg/m ³ |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version
1.1AU

DE / EN

Revision Date:
04.09.2024

Date of last issue: 21.09.2023
Date of first issue: 29.07.2022

| | | | | |
|--|--|--|---------|--|
| | | | effects | |
|--|--|--|---------|--|

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|----------------|------------------------------|-------------------------------|
| ethyl acetate | Fresh water | 0,24 mg/l |
| | Sea water | 0,024 mg/l |
| | Fresh water sediment | 1,15 mg/kg dry weight (d.w.) |
| | Sea sediment | 0,115 mg/kg dry weight (d.w.) |
| | Sewage treatment plant (STP) | 650 mg/l |
| | Soil | 0,148 mg/kg dry weight (d.w.) |
| | Oral (Secondary Poisoning) | 200 mg/kg food |

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Fluorinated rubber
Break through time : > 480 min
Glove thickness : >= 0,12 mm
Directive : DIN EN 374
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Organic vapor Type (A)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.
Avoid contact with the skin and the eyes.
Use only with adequate ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

| | | |
|---------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 21.09.2023 |
| 1.1AU DE / EN | 04.09.2024 | Date of first issue: 29.07.2022 |

Environmental exposure controls

Soil : Avoid subsoil penetration.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|--|
| Physical state | : liquid |
| Color | : gray |
| Odor | : characteristic |
| Melting point/freezing point | : not determined |
| Initial boiling point and boiling range | : 77 °C |
| Flammability | : Not applicable |
| Upper explosion limit / Upper flammability limit | : 10,5 %(V) |
| Lower explosion limit / Lower flammability limit | : 0,6 %(V) |
| Flash point | : -5 °C |
| Autoignition temperature | : > 200 °C |
| pH | : not determined substance/mixture is non-soluble (in water) |
| Viscosity | |
| Viscosity, dynamic | : 690 mPa.s (20 °C) |
| Viscosity, kinematic | : not determined |
| Solubility(ies) | |
| Water solubility | : immiscible |
| Partition coefficient: n-octanol/water | : No data available |
| Vapor pressure | : 98,3 hPa (20 °C) 306 hPa (50 °C) |
| Density | : 1,04 g/cm ³ (20 °C) |

9.2 Other information

Explosives : Not explosive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

| | | |
|---------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 21.09.2023 |
| 1.1AU DE / EN | 04.09.2024 | Date of first issue: 29.07.2022 |

In use, may form flammable/explosive vapor-air mixture.

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

Acute oral toxicity : LD50 Oral (Rat): > 5.840 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 23,3 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rat): > 2.920 mg/kg

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 4.934 mg/kg
Method: OECD Test Guideline 401

CAM Anti Chip Coat grey

| | | |
|---------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 21.09.2023 |
| 1.1AU DE / EN | 04.09.2024 | Date of first issue: 29.07.2022 |

Acute inhalation toxicity : LC0 (Rat): 22,5 mg/l, > 6000 ppm
Exposure time: 6 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20.000 mg/kg

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 Oral (Rat): > 5.840 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rat): > 2.800 - 3.100 mg/kg

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 Oral (Rat): > 5.840 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 23,3 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.800 - 3.100 mg/kg

Hydrocarbons, C9, Aromatics:

Acute oral toxicity : LD50 Oral (Rat, female): ca. 3.492 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 6,193 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 3.160 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Components:**Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:**

Result : Skin irritation

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version 1.1AU DE / EN Revision Date: 04.09.2024 Date of last issue: 21.09.2023
Date of first issue: 29.07.2022

Result : Skin irritation

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9, Aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C9, Aromatics:

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version

1.1AU

DE / EN

Revision Date:

04.09.2024

Date of last issue: 21.09.2023

Date of first issue: 29.07.2022

Hydrocarbons, C9, Aromatics:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9, Aromatics:

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9, Aromatics:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

| | | |
|---------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 21.09.2023 |
| 1.1AU DE / EN | 04.09.2024 | Date of first issue: 29.07.2022 |

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

- | | | |
|--|---|---|
| Toxicity to fish | : | LL50 (Oncorhynchus mykiss (rainbow trout)): > 13,4 mg/l End point: mortality Exposure time: 96 h Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EL50 (Daphnia magna (Water flea)): 3 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 |
| Toxicity to algae/aquatic plants | : | EL50 (Pseudokirchneriella subcapitata (green algae)): 10 mg/l End point: Growth rate Exposure time: 72 h Method: OECD Test Guideline 201 |
| Toxicity to fish (Chronic toxicity) | : | NOELR: 1.534 mg/l Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout) |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOELR: 1 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211 |

ethyl acetate:

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): 230 mg/l Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 610 mg/l Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 |
| Toxicity to microorganisms | : | NOEC (Pseudomonas putida): 650 mg/l Exposure time: 16 h |
| Toxicity to fish (Chronic toxicity) | : | NOEC: > 9,65 mg/l Exposure time: 32 d |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version 1.1AU DE / EN Revision Date: 04.09.2024 Date of last issue: 21.09.2023
Date of first issue: 29.07.2022

Species: Pimephales promelas (fathead minnow)
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 2,4 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 11,4 mg/l
End point: mortality
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l
End point: Immobilization
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 10 - 30 mg/l
End point: Biomass
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 35,57 mg/l
End point: Growth rate
Exposure time: 48 h

Toxicity to fish (Chronic toxicity) : NOELR: 2.045 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 3 - 10 mg/l
End point: mortality
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 4,6 - 10 mg/l
End point: Immobilization
Exposure time: 48 h
Method: OECD Test Guideline 202

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version 1.1AU DE / EN Revision Date: 04.09.2024 Date of last issue: 21.09.2023
Date of first issue: 29.07.2022

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 10 - 30 mg/l
End point: Growth rate
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: 0,574 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C9, Aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3,2 mg/l
End point: Immobilization
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: 1,228 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 2,144 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

| | | |
|---------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 21.09.2023 |
| 1.1AU DE / EN | 04.09.2024 | Date of first issue: 29.07.2022 |

Biodegradability : Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

ethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 79 %
Related to: Biochemical oxygen demand
Exposure time: 20 d
Method: OECD Test Guideline 301D

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Biodegradability : Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Hydrocarbons, C9, Aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

ethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 0,68 (25 °C)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Partition coefficient: n-octanol/water : Remarks: No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

| | | |
|---------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 21.09.2023 |
| 1.1AU DE / EN | 04.09.2024 | Date of first issue: 29.07.2022 |

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Dispose of in accordance with local regulations.
Send to a licensed waste management company.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN / ADG : UN 1139
ADR : UN 1139
RID : UN 1139
IMDG : UN 1139
IATA : UN 1139

14.2 UN proper shipping name

ADN /ADG : COATING SOLUTION

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version 1.1AU DE / EN Revision Date: 04.09.2024 Date of last issue: 21.09.2023
Date of first issue: 29.07.2022

(Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes, ethyl acetate)

ADR : COATING SOLUTION
(Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes, ethyl acetate)

RID : COATING SOLUTION
(Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes, ethyl acetate)

IMDG : COATING SOLUTION
(Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes, ethyl acetate, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

IATA : Coating solution
(Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes, ethyl acetate)

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|-----------------|-------|------------------|
| ADN /ADG | : 3 | |
| ADR | : 3 | |
| RID | : 3 | |
| IMDG | : 3 | |
| IATA | : 3 | |

14.4 Packing group

ADN / ADG
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Remarks : Special Provision 640D

ADR
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)
Remarks : Special Provision 640D

RID
Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Remarks : Special Provision 640D

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

| | | |
|---------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 21.09.2023 |
| 1.1AU DE / EN | 04.09.2024 | Date of first issue: 29.07.2022 |

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN /ADG

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

| | | |
|---------------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 21.09.2023 |
| 1.1AU DE / EN | 04.09.2024 | Date of first issue: 29.07.2022 |

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

All ingredients of this product are registered in the AIC as required by AICIS

15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapor.
H226 : Flammable liquid and vapor.
H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H319 : Causes serious eye irritation.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H411 : Toxic to aquatic life with long lasting effects.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version

1.1AU

DE / EN

Revision Date:

04.09.2024

Date of last issue: 21.09.2023

Date of first issue: 29.07.2022

Eye Irrit.

: Eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version 1.1AU DE / EN Revision Date: 04.09.2024 Date of last issue: 21.09.2023
Date of first issue: 29.07.2022

| | | |
|--------------------|---|--|
| Flam. Liq. | : | Flammable liquids |
| Skin Irrit. | : | Skin irritation |
| STOT SE | : | Specific target organ toxicity - single exposure |
| 2017/164/EU | : | Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values |
| DE TRGS 900 | : | Germany. TRGS 900 - Occupational exposure limit values. |
| 2017/164/EU / STEL | : | Short term exposure limit |
| 2017/164/EU / TWA | : | Limit Value - eight hours |
| DE TRGS 900 / AGW | : | Time Weighted Average |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

| | |
|-------------------|------|
| Flam. Liq. 2 | H225 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2 | H319 |
| STOT SE 3 | H336 |
| Aquatic Chronic 2 | H411 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

CAM Anti Chip Coat grey

Version

1.1AU

DE / EN

Revision Date:

04.09.2024

Date of last issue: 21.09.2023

Date of first issue: 29.07.2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN